

Duplex

(Rel.77-10/98 Pub.605)

FORM 5-4

5-41

Practitioner's Docket No. 60680-730

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Black et al. Group No.: Unassigned  
Application No.: 10 /679,921:  
Filed: 10/06/03 Examiner: Unassigned  
For: PUMP

Assistant Commissioner for Patents  
Washington, D.C. 20231

TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country: United Kingdom  
Application Number: 0223516.6  
Filing Date: October 10, 2002

**WARNING:** "When a document that is required by statute to be certified must be filed, a copy, including a photocopy or facsimile transmission of the certification is not acceptable." 37 C.F.R. § 1.4(f) (emphasis added).

SIGNATURE OF PRACTITIONER

Reg. No. 41,908

William F. Kolakowski III

(type or print name of practitioner)  
Dykema Gossett PLLC  
39577 Woodward Avenue

Tel. No. (248) 203-0822

P.O. Address Suite 300  
Bloomfield Hills, MI 48304-2820

Customer No.: 26127

**NOTE:** The claim to priority need be in no special form and may be made by the attorney or agent, if the foreign application is referred to in the oath or declaration, as required by § 1.63.

CERTIFICATE OF MAILING (37 C.F.R. § 1.8a)

I hereby certify that this correspondence is, on the date shown below is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.


Date: 01/02/04

Signature

Linda K. Caragay  
(type or print name of person certifying)

(Transmittal of Certified Copy [5-4])





INVESTOR IN PEOPLE


The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.





Signed *He Behen*

Dated 30 September 2003



# Patents Form 1/77

Patents Act 1977  
(Rule 16)



10 OCT 02 0754493-0 002811  
P01/7700 0.00-0223516.6  
**1/77**

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

A10531GB-DJL/SCL/scf

2. Patent application number

(The Patent Office will fill in this part)

**0223516.6**

10 OCT 2002

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)

Dana Automotive Limited  
Wood Lane  
Erdington  
Birmingham  
B24 9QS

Patents ADP number (*if you know it*)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

083383 86002

4. Title of the invention PUMP

5. Name of your agent (*if you have one*)

Forrester Ketley & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

Chamberlain House  
Paradise Place  
Birmingham  
B3 3HP

Patents ADP number (*if you know it*)

133005

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number  
(*if you know it*)

Date of filing  
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(*day / month / year*)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

Yes

## Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

8 ✓

Claim(s)

3 ✓

Abstract

1 ✓

Drawing(s)

3 + 3 2

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature *Forrester Ketley & Co* Date

9 October 2002

Forrester Ketley & Co.

12. Name and daytime telephone number of person to contact in the United Kingdom

D J Lucking  
0121 236 0484

### Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

DUPLICATE

PATENTS ACT 1977

A10531GB-DJL/ACL

Title: Pump

Description of Invention

The present invention relates to a pump, particularly, but not exclusively for use in pumping lubricant such as oil into an engine.

Conventionally, a positive displacement pump such as a gear pump or gerotor is used to pump a liquid lubricant such as oil in an engine. When the engine is cold, on start-up for example, the oil is relatively viscous, and pumping oil of such high viscosity with a conventional positive displacement pump is not only inefficient, but when the pump is electrically driven, this can put the pump motor under undesirable strain.

According to a first aspect of the invention we provide a pump including a driving part and a pumping part, the pumping part including a plurality of generally parallel planar elements mounted for rotation about a first axis, wherein the driving part is coupled to the pumping part by means of a magnetic coupling device such that rotation of the driving part causes rotation of the pumping part about the first axis.

A pump in which liquid to be pumped is moved by a plurality of generally parallel planar elements such as discs or annular plates will hereinafter be referred to as a disc pump. An advantage of a disc pump is that the efficiency of such a pump is greater when the viscosity of the pumped liquid is greater. Thus, a disc pump most advantageously may be used in the invention to pump high viscosity liquid such as cold oil.

Moreover, by virtue of coupling the driving part to the pumping part by means of a magnetic coupling device, slip may occur between the driving part and pumping part if the torque necessary to rotate the pumping part exceeds a threshold value. Thus, where the driving part is motor driven, the possibility of

the motor being damaged as a result of it being placed under strain when pumping high viscosity liquid is reduced.

Preferably, the magnetic coupling includes a first coupling part which is connected to the driving part for rotation with the driving part, and a second coupling part which is connected to the pumping part for rotation with the pumping part, one of the first or second parts including a magnet, and the other of the first or second parts including an electrically conductive part.

Preferably the first coupling part and second coupling part are mounted for rotation about the first axis.

Preferably, the magnet is a permanent magnet.

The magnet may have a side wall which encloses a generally cylindrical space, and the electrically conductive part may be generally cylindrical and may be located at least partly within the wall of the magnet.

The electrically conductive part of the magnetic coupling may include a plurality of elongate copper elements arranged in a generally circular array around an axis of rotation of the first part of the magnetic coupling, a longitudinal axis of each copper element being generally parallel to the axis of rotation. The electrically conductive part may also include two generally annular copper plates which are mounted on either side of the copper elements in contact with end portions of all the copper elements. The electrically conductive part may also include a soft iron core.

Preferably the second coupling part is, in use, immersed in the liquid to be pumped, and a sealing part is provided between the first and second coupling parts, the sealing part substantially preventing pumped liquid from contacting the first coupling part and the motor.

Preferably the pumping part includes a plurality of generally parallel, co-axial discs.

According to a second aspect of the invention we provide an engine including a lubricant pump according to the first aspect of the invention.



According to a third aspect of the invention we provide a lubrication system for an engine including two lubricant pumps, one of which is a pump according to the first aspect of the invention which is adapted to pump lubricant on start-up of the engine.

By virtue of the viscosity of lubricant such as oil decreasing with increasing temperature, the pump of the invention lends itself particularly for use pumping lubricant in an engine. Whereas the efficiency of the disc pump decreases as temperature rises to a usual working temperature, the amount of slip of the magnetic coupling alone will decrease as less torque is imposed on the driving part.

The invention will now be described with reference to the accompanying drawings of which,

FIGURE 1 illustrates a cross-section through a pump according to the invention, and

FIGURE 2 illustrates an exploded perspective view of the magnetic coupling and sealing part of the pump of figure 1,

FIGURE 3 is a schematic illustration of a lubrication system according to the third aspect of the invention.

Referring to the figures, there is shown a pump 10, typically for use in pumping lubricating oil in an automotive engine. The pump 10 includes a driving part 12, which in this case is the output shaft 12 of an electric motor 18, and a pumping part 14, hereinafter referred to as a disc pack 14, the disc pack 14 including a plurality of co-axial, generally parallel discs 16. Typically, the motor 18 is an electric motor, but any other type of motor 18 may be used. The output shaft 12 of the motor 18 is coupled to the disc pack 14 by means of a magnetic coupling 20.

The magnetic coupling 20 includes a first coupling part 22 which is connected to the motor output shaft 12 and which is mounted for rotation with

the output shaft 18 about an axis A, and a second coupling part 24 which is connected to the disc pack 14 and mounted for rotation with the disc pack 14.

The first coupling part 22 includes a magnet 26, in this case a permanent magnet, with a circular base 26a and a side wall 26b which encloses a generally cylindrical space. The motor output shaft 12 is connected to the base 26a generally at the centre of the base 26a such that the side wall 26b extends axially away from and generally parallel to the output shaft 18.

The second coupling part 24 is generally cylindrical and includes an electrically conductive part with plurality of copper bars 28a arranged in a generally circular array around the axis of rotation A. The bars are spaced from one another with a longitudinal axis of each of the bars 28a parallel to the axis of rotation A. The copper bars 28a are mounted between two annular copper plates 28b such that both ends of each copper bar 28a are in contact with a copper plate 28b. The copper plates 28b are normal to and centred around the axis of rotation A, and provide an electrical connection between the copper bars 28a. The bars 28a and plates 28b are supported on a soft iron core 28c.

The second coupling part 24 is mounted around a cylindrical bearing shaft 30 for rotation about the bearing shaft 30. The bearing shaft 30 extends along the axis A, and the second coupling part 24 is rigidly connected to the disc pack 14 such that the second coupling part 24 and disc pack 14 may rotate together about axis A. In this example, the disc nearest the coupling 20 is bolted to the second coupling part 24, but the second coupling part 24, may alternatively be welded to the disc pack 14, or moulded as an integral part of the disc pack 14.

The motor output shaft 12 and magnetic coupling 20 are contained within a generally cylindrical housing 32 which extends from a casing 18a of the motor 18. The housing 32 has four wings 32a which extend radially outwardly from the housing 32 to which are bolted, at an end of the housing 32 opposite the motor 18, a volute 34 with an inlet port 34a and an outlet port 34b,

the disc pack 14 being contained within the volute 34. The volute 34 is of a conventional spiral configuration with the inlet port 34a located generally centrally of the volute 34 and extending generally along the axis of rotation A of the second coupling part 24 and the disc pack 14, and the outlet port 34b extending tangentially outwardly from the periphery of the volute 34.

There is also provided a sealing part 36 which has a circular base 36a, a side wall 36b enclosing a generally cylindrical space, and a lip 36c which extends outwardly from an end of the side wall 36b opposite to the base 36a. The sealing part 36 is located between the first coupling part 22 and the second coupling part 24, the base 36a being adjacent to the base 26a of the first coupling part 22. The second coupling part 24 extends into the space enclosed by the side wall 36b of the sealing part 36, and the sealing part 36 extends into the space enclosed by the side wall 26b of the first coupling part 22. Thus the side wall 26b of the first coupling part 26 encloses the second coupling part 24, but the two are separated by the sealing part 36.

The base 36a of the sealing part 36 includes a generally central recess in which the bearing shaft 30 is located. The bearing shaft 30 may also be supported at its end nearest the disc pack 14.

The lip 36c of the sealing part 36 is sandwiched between the housing 32 and the volute 34, and provides a substantially liquid tight seal between the first and second coupling parts 22, 24. The sealing part 36 is made from an electrically non-conductive material, and is typically polymeric.

In use, pumped fluid may flow from the volute 34 into part of the housing 32, and may flow around the second coupling part 24. The sealing part 36 substantially prevents the fluid from flowing around the first coupling part 22 and the motor output shaft 12, and hence pumped fluid does not come into contact with the motor 18.

The oil pump 10 operates as follows.

Activation of the motor 18 causes the motor output shaft 12 and hence the first coupling part 22 to rotate about axis A. Rotation of the magnet 26 induces eddy currents in the copper bars 28a and plates 28b of the second coupling part 24, and the eddy currents produce a magnetic field. The magnetic field produced by the eddy currents interacts with that of the magnet 26, and as a result of this interaction, the second coupling part 24 rotates with the first coupling part 22.

Rotation of the second coupling part 24 causes the disc pack 14 to rotate, and shear forces in the oil between the discs of the disc pack cause the oil to be pulled around the volute 34 and pumped out of the outlet port 34b. As transfer of rotational energy from the disc pack 16 to the oil arises due to viscous drag, the efficiency of pumping decreases with decreasing oil viscosity. Thus, the efficiency of pumping decreases as the engine warms up, and the pump is particularly useful for pumping oil when the oil is cold.

If, however, the fluid is so viscous that the torque required to rotate the disc pack 14 exceeds a threshold value, the magnetic coupling 20 will slip such that the second coupling part 24 rotates at a lower speed than the first coupling part 22. This is possible because the first coupling part 22 is not mechanically connected to the second coupling part 24. Slip may occur, for example, when pumping cold oil on engine start-up.

The threshold value of the torque before slip occurs can be determined by providing the first coupling part 22 with a magnet 26 of an appropriate strength. The stronger the magnetic field produced by the magnet 26, the higher the maximum value of torque transferred. Slip of the magnetic coupling 20 assists in protecting the motor 18 from damage through turning against excessive torque.

When the pump 10 is used for pumping lubricating oil into an automotive engine, as the engine warms up, the viscosity of the oil decreases, and hence the efficiency of the disc pack 14 in pumping the oil decreases. The

torque required to rotate the disc pack 14 decreases, however, and thus slip between the first and second coupling parts 22, 24 is reduced if not eliminated. Thus as the efficiency of the disc pack 14 in pumping fluid decreases, the efficiency of the coupling 20 in transferring motive power from the motor 18 to the disc pack 16 increases.

A pump 10 according to the first aspect of invention may be used instead of a conventional oil pump in an engine such as an automotive engine, or may be used in a lubrication system as a supplementary pump to pump oil when the engine is cold. An example of such an engine lubrication system is illustrated in Figure 3, and includes a supplementary pump 10 according to the first aspect of the invention, and a main pump 40 which is a conventional engine lubrication pump such as a positive displacement pump, both of which are adapted to pump lubricant, such as oil, from a lubricant reservoir 42 into the engine 44.

A control device 48 is also provided, the control device 48 being adapted to select which pump 10, 40 is to be used to pump lubricant into the engine 44. On engine start-up, when the engine is cold, the control device 48 is adapted to select the supplementary pump 10, and when the engine approaches its usual working temperature, the control device 48 is adapted to switch to select the main pump 40 instead of or in addition to the supplementary pump 10. The control device 48 may be adapted to switch between pumps 10, 40, or the pumps 10, 40 may operate simultaneously, for example during a transition period, as desired. The control device 48 may be adapted to control flow of power to the pumps 10, 40 and/or flow of lubricant to the pumps 10, 40.

The pump 10 need not be driven by a motor 18. It may instead be driven by means of a power take-off from the engine for which the pump is providing lubrication.

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in

terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS

1. A pump including a driving part and a pumping part, the pumping part including a plurality of generally parallel planar elements all mounted for rotation about a first axis, wherein the driving part is coupled to the pumping part by means of a magnetic coupling device such that rotation of the driving part causes rotation of the pumping part about the first axis.
2. A pump according to claim 1 wherein the magnetic coupling includes a first coupling part which is connected to the driving part for rotation with the driving part, and a second coupling part which is connected to the pumping part for rotation with the pumping part, one of the first or second parts including a magnet, and the other of the first or second parts including an electrically conductive part.
3. A pump according to claim 2 wherein the first coupling part and second coupling part are mounted for rotation about the first axis.
4. A pump according to claim 2 or 3 wherein the magnet is a permanent magnet.
5. A pump according to any one of claims 2 to 4 wherein the magnet has a side wall which encloses a generally cylindrical space, and the electrically conductive part is generally cylindrical and is located at least partly within the wall of the magnet.
6. A pump according to claim 5 wherein the electrically conductive part of the magnetic coupling includes a plurality of elongate copper elements arranged in a generally circular array around an axis of rotation of the first part of the

magnetic coupling, a longitudinal axis of each copper element being generally parallel to the axis of rotation.

7. A pump according to claim 6 wherein the electrically conductive part includes two generally annular copper plates which are mounted on either side of the copper elements in contact with end portions of all the copper elements.

8. A pump according to claim 6 or 7 wherein the electrically conductive part includes a soft iron core.

9. A pump according to any one of claims 2 to 8 wherein the second coupling part is, in use, immersed in the liquid to be pumped, and a sealing part is provided between the first and second coupling parts, the sealing part substantially preventing pumped liquid from contacting the first coupling part and the motor.

10. A pump according to any preceding claim wherein the pumping part includes a plurality of generally parallel, co-axial discs.

11. A pump substantially as hereinbefore described with reference to and/or as shown in the accompanying drawings.

12. An engine including a lubricant pump according to claim 1.

13. An engine substantially as hereinbefore described with reference to the accompanying drawings.



14. A lubrication system for an engine including two lubricant pumps, one of which is a pump according to claim 1 which is adapted to pump lubricant on start-up of the engine.


15. A lubrication system substantially as hereinbefore described with reference to and/or as shown in the accompanying drawings.

16. Any novel feature or novel combination of features hereinbefore described and/or shown in the accompanying drawings.

## ABSTRACT

Title: Pump

A pump (10) including a driving part (12) and a pumping part (14), the pumping part (14) including a plurality of generally parallel planar elements (16) all mounted for rotation about a first axis (A), wherein the driving part (12) is coupled to the pumping part (14) by means of a magnetic coupling device (20) such that rotation of the driving part (12) may cause rotation of the pumping part (14) about the first axis (A).







2 / 3






FIG. 2





3 / 3




FIG 3

